

# JC-3200

## Desktop Automatic Card Counter

- ✓ Government
- ✓ Banking
- ✓ Healthcare
- ✓ Education
- ✓ Hospitality
- ✓ Corporate
- ✓ Retail
- ✓ Manufacturing
- ✓ Transportation, warehousing and more



### Card counting the easy way

- Auto-scan 0.28mm – 1.5mm un-embossed and embossed cards with circuitry-verification feature
- Large LCD display with voice reporting
- Photo electric sensor and circulation
- ISO certification

**Batch,  
counts and  
totals cards,  
tickets and  
more in  
seconds**

### Advanced digital scan technology,

electro-optical components and precise logical circuits. Two independent calculation circuits automatically scan cards and verify the results.

Counts cards from 0.28mm; laminated or non-laminated. A big LCD display, maximum accumulation of 99,999 pcs, and vocal report make it easier and more user-friendly. Model JC-

3200C compressed air preparation technology allows a wider range of cards to be counted.

Applications include Banking, Pay TV, Healthcare, GSM, Pre-cards, Corporate and government ID, Retail/Loyalty, Transit, Sports, Student ID, Membership/Credit cards, Hotel key cards—and more.

click here  
**WATCH  
HOW IT  
WORKS**



## More material types and sizes with JC-3200C Air-jet function

The JC-3200C model connects to a compressed air supply. An air jet delivers a concentrated flow of air that separates cards during the counting process. This make the JC-3200C particularly proficient at counting thin plastic and paper cards

### Benefits

- Quick and accurate counting results
- Easy card loading to card magazine
- Cost-effective & durable performance
- Custom/ OEM solutions and environmentally and user friendly operation

### Technical Features

JC-3200A	JC-3200C
▪ AC Input: 200~240V, 50~60HZ, 1A	▪ AC Input: 200~240V, 50~60HZ, 1A
▪ Power Consumption: ≤25W	▪ Power Consumption: ≤25W
▪ <b>Working Environment:</b> Humidity: 30% – 90% Temperature: 32°F – 104°F (0°C – 40°C)	▪ <b>Working Environment:</b> Humidity: 30% – 90% Temperature: 32°F – 104°F (0°C – 40°C)
▪ Thickness: 0.5-1.5mm	▪ Thickness: 0.28 -1.5mm with Air Compression
▪ Counting Speed: 500 cards / 4 seconds (standard card 0.76mm)	▪ Counting Speed: 500 cards / 4 seconds (standard card 0.76mm)
▪ LED Display with Voice Reporting	▪ LED Display with Voice Reporting
▪ Maximum Accumulation: 99,999 cards	▪ Maximum Accumulation: 99,999 cards
▪ Interface: RS-232C (Optional)	▪ Interface: RS-232C (Optional)
▪ Dimensions: 650(L) x 220(W) x 280(H) mm	▪ Dimensions: 650(L) x 220(W) x 280(H) mm
▪ Net Weight: 40 LB (18 KG)	▪ Net Weight: 40 LB (18 KG) with air compression

### Videos

- [www.youtube.com/watch?v=cB1Xfzcz97E](http://www.youtube.com/watch?v=cB1Xfzcz97E) : [www.youtube.com/watch?v=SgLB74-siN4](http://www.youtube.com/watch?v=SgLB74-siN4)